

SRD991-BHFS7NFMNY-V02 Intelligent Positioner (Intrinsically Safe)

Code	Category	Description
SRD991	FUNCTION	Intelligent Positioner SRD991 certified Ex ia/Intrinsically Safe or not, with advanced diagnostics. Operates pneumatic valve actuators. Input Signal: 4-20 mA / HART / PROFIBUS-PA / FOUNDATION Fieldbus H1 (FISCO compliant).
B	VERSION	Single Acting
H	INPUT/COMMUNICATION	HART Communication (4-20 mA)
F	ADDITIONAL INPUTS/OUTPUTS	Position Feedback 4-20 mA and one Binary Output
S	BUILT-IN LIMIT SWITCH	Without
7	CABLE ENTRY	M20 x 1.5 with one plastic Cable Gland
NFM	ELECTRICAL CERTIFICATION	FM Nonincendive for Class I, Division 2, Groups A,B,C,D. Hazardous Locations Indoors and Outdoors, NEMA 4X
N	ATTACHMENT KIT	Order as auxiliary
Y	MANIFOLD	Pneumatic connection 1/4 - 18 NPT made of an additional manifold
V02	OPTIONAL MODEL SUFFIX(ES)	LCD with Menu-Language in English / German / Spanish